

## Connection boxes

<p><b>HM-PCB0</b></p> <p>Connection box usable for 1 mineral insulated heating cable or 1 heating tape</p> <p>technical data: dimensions: 125 x 80 x 65 mm (w x h x d)</p> <p>order-no.: 70000000</p>	<p>material: fiberglass polyester protection system: IP 65 colour: grey RAL7000 temperature range: -40°C - +100°C bore holes: 2 x M 20 x 1,5 glands: 1 x M 25 complimentary parts: 2 x 10 mm<sup>2</sup> Uk10 1 x 10 mm<sup>2</sup> USLKG10</p>
---	---



<p><b>HM-PCB1</b></p> <p>Connection box usable for 2 mineral insulated heating cable or 2 heating tapes</p> <p>technical data: dimensions: 122 x 120 x 90 mm (w x h x d)</p> <p>order-no.: 70000001</p>	<p>material: fiberglass polyester protection system: IP 65 colour: grey RAL7000 temperature range: -40°C - +100°C bore holes: 4 x M 20 x 1,5 glands: 1 x M 25 complimentary parts: 4 x 10 mm<sup>2</sup> Uk10 2 x 10 mm<sup>2</sup> USLKG10 blanking plug: 3 x M 20 loose</p>
---	---



<p><b>HM-PCB2</b></p> <p>Connection box usable for 3 mineral insulated heating cable or 3 heating tapes</p> <p>technical data: dimensions: 220 x 120 x 90 mm (w x h x d)</p> <p>order-no.: 70000002</p>	<p>material: fiberglass polyester protection system: IP 65 colour: grey RAL7000 temperature range: -40°C - +100°C bore holes: 6 x M 20 x 1,5 glands: 1 x M 25 complimentary parts: 6 x 10 mm<sup>2</sup> Uk10 3 x 10 mm<sup>2</sup> USLKG10 blanking plug: 2 x M 20 loose</p>
---	---



<p><b>HM-PCB5</b></p> <p>Connection box usable for 1 mineral insulated heating cable or 1 heating tape</p> <p>technical data: dimensions: 95 x 95 x 57 mm (w x h x d)</p> <p>order-no.: 70000005</p>	<p>material: fiberglass polyester protection system: IP 65 colour: grey RAL7000 temperature range: -40°C - +100°C bore holes: 2 x M 20 x 1,5 glands: 1 x M 25 complimentary parts: 2 x 10 mm<sup>2</sup> Uk10 1 x 10 mm<sup>2</sup> USLKG10</p>
--	---

