

Professional heating technology for
industry and laboratory applications

MOHR & CO
Laborhandels-gesellschaft mbH

Bottom heater series HM-DBH-200 and HM-DBH-500

for operating temperatures up
to 200°C / 500°C



Description:

Connection-ready, stable bottom heater, design for standard 200l-barrel.

This bottom heater can use in combination with our barrel heater for a shorter heating time. The design with stainless steel metal sheet guaranteed a heavy-duty construction as also stability under hard operational conditions.

With the integrated temperature regulation it may can regulate a temperature up to 200°C or 500°C.

Features:

- faster heating time
- no additional insulation necessary
- low surface load
- stable, robust construction
- high-quality stainless-steel construction



Technical data

HM-DBH-200

voltage	230 V AC
power	see order data
dimension	Ø 510 x 85 mm
material	stainless steel
protection class	I
protection system	water-jet proof to IP 65
temperature controller	capillary controller 0 – 200°C
max. heating temperature	200°C
length main-cable	2,0 m with schuko-plug

Technical data

HM-DBH-500

voltage	230 V AC
power	see order data
dimension	Ø 510 x 85 mm
material	stainless steel
protection class	I
protection system	water-jet proof to IP 65
temperature controller	capillary controller 0-500°C
max. heating temperature	500°C
length main-cable	2,0 m with schuko-plug

Order data

type	power W	order.-no.
HM-DBH-200	1150	51000300
HM-DBH-500	2000	51000305

Other dimensions, voltages and performances - available on request



Drum heating jacket
HM-HJD-250S-450



Drum heating mat
HM-HMD-200



Drum band heater HM-SMF

MOHR & CO
Laborhandels-gesellschaft mbH

D-69181 Leimen
Gottlieb-Daimler-Straße 2

Phone + 49 (0) 6224 7 10 93 + 94
Fax + 49 (0) 6224 7 70 12

info@labo-mohr.de
www.labo-mohr.de