

Capillary tube thermostat HM-CST series



Description:

The particularly robust, electromechanical surface thermostat can be used wherever simple constant product temperatures are required. A transparent cover protects against unintentional adjustment of the temperature setting.

Features:

- Sturdy polycarbonate housing with transparent cover
- Indicator light for mains and operation
- temperature setting visible from outside
- direct connection of supply line and heating possible
- Switching capacity up to 16 A
- Screw connection 3 x M20
- Capillary tube length controller approx. 2 m

Technical data

HM-CST

nominal voltage	230 V AC
switching power	3650 W
switching current	16 A
temperature range	see order data
capillary tube length	ca. 2 m
capillary tube material	CU
switching differential	2,5 %
protection class	I
protection type	IP 65
screw fittings	3 x M20
dimensions	170 x 140 x 100 x mm (B x H x T)

Order data

type	temperature range	order-no.
HM-CST 40	-20 - +40°C	60000040
HM-CST 200	0 - 200°C	60000200
HM-CST 300	50 - 300°C	60000300

Other temperature regulators on request



Temperature regulator
HM-EC 210



Electronic temperature
regulator HM-RD 1000



Double temperature
regulator HM-RD 2000



Regulator- and limiter-
combination HM-RD 3000

MOHR & CO

Winkler AG
D-69181 Leimen

Gottlieb-Daimler-Straße 2
Tel. + 49 (0) 6224 7 10 93 + 94

mohr@labo-mohr.de
www.labo-mohr.de