

Silicone heating tape series HM-HT-201

for surface temperatures up to 200°C



Description:

Ready-made and very flexible silicone heating tape of highest quality. The heating conductors are surrounded by high-quality silicon rubber.

Features:

- protected against spray water
- particularly flexible heating band
- easy to clean – due to its smooth surface, recommendable particularly where food is produced and stored

Applications:

In addition to the heating of formed parts or narrow pipes, this short standard heating band is also meant for continuous use in laboratories and in technology, where trial constructions are produced in general.

Technical data

HM-HT-201

nominal voltage	230 V AC
nominal power	see order data
dimensions	14 x 4 mm
min. bending radius	> 4 mm
installation intervall	> 10 mm
protection class	0
protection system	IP 67 (protected against spray water)
surface temperature (switched on)	200°C
connection cable (silicone-insulated)	1,5 m für Festanschluss

Order data

length m	power W	order no.
0,9	100	15100009
1,8	200	15100018
2,7	260	15100027

Other lengths available on request

Accessories

Terminal boxes, matching assembly consoles and assembly materials upon request.

For temperature regulation we suggest our program of electronic control and temperature regulation appliances and corresponding temperature sensors.



Electronic temperature regulator HM-EC 210



Power controller HM-L 116



Electronic laboratory regulator HM-RX 1000



Temperature sensors

MOHR & CO

Winkler AG
D-69181 Leimen

Gottlieb-Daimler-Straße 2
Tel. + 49 (0) 6224 7 10 93 + 94

mohr@labo-mohr.de
www.labo-mohr.de